# MATERIAL SAFETY DATA SHEET

**Supplier:** SUPERSEAL Construction Products Ltd.

PO Box 61646, Brookswood RPO

Langley, BC V3A 8C8 Canada

Phone: 1-800-571-1877 Fax: 1-604-856-2447

Plants: 26019 31b Ave

Aldergrove, BC V4W 2Z6

# THIS PRODUCT IS NOT SUBJECT TO THE CONTROLLED PRODUCTS OR THE TRANSPORTATION DANGEROUS GOODS REGULATIONS

## SECTION 1 MATERIAL IDENTIFICATION

TRADE NAME: SUPERPRO Waterproofing

CHEMICAL FAMILY: Water suspension of petroleum derived hydrocarbons (poly

modified emulsifed asphalt) and inert fillers.

MATERIAL USE: Protective Coating

T.D.G. CLASSIFICATION: NON REGULATED

WHIMIS CLASSIFICATION: NON REGULATED

**EMERGENCY TELEPHONE #**: 1-800-571-1877

#### **SECTION II HAZARDOUS INGREDIENTS**

COMPONENT	CA	S#	% (BY MASS)	LC50 (ppm) (rat inhal)	LD50 (mg/kg) (rat oral)
Complex mixture of bitumens	n/a		40-70	n/a	n/a
surfactants	n/a		0.5-2.0	n/a	n/a
water	7732	-18-5	30-60	n/a	n/a
Polymer dispersion			5-25	n/a	n/a

# **SECTION III PHYSICAL PROPERTIES**

Odour and appearance: Brown liquid, slight resinous odour.

Odour threshold: n/a

Specific gravity: 1.00 (approx.).

Coefficient of water/oil distribution: n/a Vapour pressure (mm Hg): 17 @20°C (water)

**Boiling point:** 100°C (water)

Freezing point: 0°C

**pH**: 7-9

Vapour density (air = 1): >1

Evaporation rate (nBuAcetate = 1): <1

Volatiles %: 40-60 (water)

Solubility in water: partially soluble

## **SECTION IV FIRE & EXPLOSION DATA**

Means of extinction: n/a

Sensitivity to mechanical impact/static discharge: n/a

Flash point (method): n/a (non-combustible)

Upper flammable limits %: n/a Lower flammable limits %: n/a Autoignition temperature: n/a

Special fire fighting instructions: n/a

Unusual fire and explosion hazards: Product will not burn but may splatter if temperature

exceeds the boiling point.

## **SECTION V REACTIVITY DATA**

Chemical stability: Stable

**Incompatible materials:** Will react with alkaline sensitive materials such as acids and certain metals. Contact with reactive metals such as aluminium or magnesium will result in the formation of explosive hydrogen gas.

**Hazardous decomposition products:** Avoid heating above 200°C. At elevated temperatures hazardous vapours can be released, including carbon monoxide, hydrogen chloride, organic acids and aldehydes.

Hazardous polymerization: Will not occur.

#### SECTION VI HEALTH INFORMATION

Exposure limit: n/a Inhalation: n/a Skin: adhesion

Eyes: adhesion, irritation.

**Ingestion:** Blockage of digestive and/or respiratory tract.

Chronic effects: n/a

## **EMERGENCY AND FIRST AID PROCEDURES**

Inhalation: n/a

**Skin:** This is an alkaline product. If splashed on the skin immediately wash thoroughly with fresh water. If the product has dried on the skin massage the area with medical grade mineral oil, baby oil or edible oil, then wash with soap and water. If irritation persists seek medical attention..

Eyes: Flush thoroughly with fresh water for at least ten minutes. Seek medical attention.

Ingestion: DO NOT INDUCE VOMITING. Seek medical attention.

#### SECTION VII SPILL PROCEDURES

In the event of a spill: Dike and contain, transfer to containers for recovery or disposal. Keep out of sewers.

Waste disposal method: Follow federal, provincial and local regulations regarding disposal.

#### SECTION VIII SPECIAL PROTECTION

Respiratory protection: n/a

Ventilation: n/a

Protective gloves: Recommended

Eye protection: safety glasses/splash goggles recommended

Other protective equipment: Long sleeves, loose clothing recommended.

#### SECTION IX SPECIAL PRECAUTIONS

**Storage and handling conditions:** Keep containers tightly closed when not in use. KEEP FROM FREEZING.

**Special shipping information:** Not regulated by the Transportation of Dangerous Goods Regulations.

Prepared by: **SUPERSEAL** Construction Products Ltd.

Preperation Date: October 15, 2011

The information contained herein is based on available data and is provided for information only. **SUPERSEAL** Construction Products Ltd. makes no warranties, guarantees or conditions, expressed or implied, regarding the accuracy of the data or it's use therein. **SUPERSEAL** Construction Products Ltd. will not be liable for any damages arising from the use of the information or product described on this sheet.